

Track mounted LED spot lamp. Body is made of steel and aluminium and it is available in all RAL colours. Light source - GE Infusion LED module. Standard EVG ballast, Touch DALI version on request.

Available optics with following beam angle:

- for 2000 lm version: 25°, 34°, 59°
- for 3000 lm version: 28°, 34°, 61°.

High quality, energy efficient white LED light with CRI 80 and more. 3 colour temperatures (2700K, 3000K, 4000K), long lifetime (50,000 hours) and no IR or UV radiation.

Applications:

- Retail: shop windows, wall - washing, accent and display lighting
- Hospitality: lobbies, reception areas, restaurants, bars
- Recreation: museums, galleries, theatres and other public places



Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Weight
0000-003403.GE2000/827	1800 lm	29W	2700K	>80	50,000 h	1,65 kg
0000-003403.GE2000/830	2000 lm	29W	3000K	>80	50,000 h	1,65 kg
0000-003403.GE2000/930	1700 lm	29W	3000K	>87	50,000 h	1,65 kg
0000-003403.GE2000/840	2200 lm	29W	4000K	>80	50,000 h	1,65 kg
0000-003403.GE3000/827	3000 lm	46W	2700K	>80	50,000 h	1,65 kg
0000-003403.GE3000/830	3200 lm	46W	3000K	>80	50,000 h	1,65 kg
0000-003403.GE3000/930	2800 lm	46W	3000K	>87	50,000 h	1,65 kg
0000-003403.GE3000/840	3500 lm	46W	4000K	>80	50,000 h	1,65 kg

